



# ALPINE SNOWGUARDS

A Division of Vermont Slate & Copper Services, Inc.

## #215 Snowguard Specification Sheet

### PART 1 - GENERAL

- 1.1 SUMMARY
- A. WORK INCLUDES
1. #215 Snowguard that attaches directly to the roof deck.
  2. Provide appropriate snowguard and fasteners for the roof system.
- B. RELATED SECTIONS
1. Section 07600: Flashing and Sheet Metal.
  2. Section 07500: Membrane Roofing
  3. Division 7: Thermal and Moisture Protection.
- 1.2 SYSTEM DESCRIPTION
- A. COMPONENTS:
1. #215 Snowguard system consists of snowguard bracket and base plate
  2. Aluminum tubing.
  3. Threaded Couplings.
  4. End Caps (optional).
  5. End Collars (optional).
  6. Fasteners
    - a. To be of metal compatible with snowguards.
    - b. Fasteners should be selected for compatibility with the roof deck.
    - c. Fastener strength should exceed or be equal to that of the snowguard system.
  7. Adhesive: to be membrane roof manufacturer approved.
- B. DESIGN REQUIREMENTS:
1. Spacing to be recommended by manufacturer or building engineer.
  2. Fasteners into the roof deck or structure must meet or exceed a combined 2000 pounds of shear.
  3. A minimum of 6 fasteners per snowguard.
  4. It is important to design new structures or assess existing structures to make sure that they can withstand retained snow loads.
- 1.3 SUBMITTAL - Submit manufacturer's specifications, standard detail drawings, recommended layout and installation instructions.
- 1.4 QUALITY ASSURANCE - Installer to be experienced in the installation of specified roofing material and snowguards for not less than 5 years in the area of the project.
- 1.5 DELIVERY / STORAGE / HANDLING - Inspect material upon delivery and order replacements for any missing or defective items. Keep material dry, covered and off the ground until installed.

### PART 2 - PRODUCTS

- 2.1 MANUFACTURER
- A. Alpine SnowGuards. A division of Vermont Slate & Copper Services Inc., P.O. Box 430, Stowe, VT (888) 766-4273.
- 2.2 MATERIALS
- A. Snowguard Block and Flag are extruded and milled 6061-T6 Aluminum
- B. Base Plate is 11 gauge thick 302 Stainless Steel.
- C. Tubing is 6005-T5, 1" outside diameter and 1/8" wall thickness extruded Aluminum.
- D. Threaded Couplings are 6061-T6 Aluminum 5" long.
- E. End Caps are 302 stainless steel.
- F. Ice Flags are 6061-T6 Aluminum 3" x \_ (as needed).
- G. End Collars are 6061 T-6 aluminum shaft collars.
- H. Fasteners are 302 or 304 Stainless Steel.
- 2.3 FINISH - All materials provided mill finish.

### PART 3 - EXECUTION

- 3.1 EXAMINATION
- A. Substrate: Inspect roof system to be properly attached and installed to withstand additional loading incurred. Notify General Contractor of any deficiencies before installing Alpine SnowGuards.
- 3.2 INSTALLATION
- A. Comply with architectural drawings for location and with Manufacturer's instructions for installation.

Document Version 01.25.2002

Mail To:  
P.O. Box 430  
Stowe, VT 05672-0430

Toll Free Phone 1.888.766.4273 Toll Free Fax 1.888.766.9994  
[www.alpinesnowguards.com](http://www.alpinesnowguards.com)  
Email [info@alpinesnowguards.com](mailto:info@alpinesnowguards.com)

Ship To:  
289 Harrell Street  
Morrisville, VT 05661